



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : F16L 3/00	A1	(11) International Publication Number: WO 00/39493 (43) International Publication Date: 6 July 2000 (06.07.00)
<p>(21) International Application Number: PCT/US99/30733</p> <p>(22) International Filing Date: 21 December 1999 (21.12.99)</p> <p>(30) Priority Data: 60/113,742 23 December 1998 (23.12.98) US</p> <p>(71)(72) Applicants and Inventors: MOSCOVITCH, Jerry [CA/CA]; 59 Cowar Avenue, Toronto, Ontario M6K 2N1 (CA). HALL, Ian, C. [CA/CA]; Unit #93, 1055 Shawmarr Road, Mississauga, Ontario L5H 3V2 (CA). CHUNG, Son [CA/CA]; 127 Lotherton Pathway, Toronto, Ontario MCB 2G6 (CA). ELCHUK, Mark, D. [US/US]; 4845 Davis Court, Troy, MI 48098 (US).</p> <p>(74) Agents: ELCHUK, Mark, D. et al.; Harness Dickey & Pierce P.L.C., P.O. Box 828, Bloomfield Hills, MI 48303 (US).</p>		<p>(81) Designated States: CA, DE, GB, JP, US.</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: COMPUTER DISPLAY SCREEN SYSTEM AND ADJUSTABLE SCREEN MOUNT, AND SWINGING SCREENS THEREFOR</p> <p>(57) Abstract</p> <p>A dual screen system (10, 12) having, a base (24), a pair of electronic display screens (16), an arm assembly (22) supporting the display screens (16) and connected to the base, and means for swingably mounting the display screens, for swinging towards one another for convenient viewing. Each of the screens (10) and (12) comprises a central rectangular display portion (16), and a rectangular marginal frame (18). The swinging means includes an arm assembly (22) which supports the display screens (16) on the base (24). The support for the arm assembly (22) from the base (24) may have an orientation relative to the base in which the display screens are positioned in vertically stacked screen relationship and may also have a different orientation in which the display screens are positioned in a horizontal, side by side relationship.</p> <div data-bbox="1092 1685 1769 2370"> </div>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

COMPUTER DISPLAY SCREEN SYSTEM AND ADJUSTABLE SCREEN MOUNT, AND SWINGING SCREENS THEREFOR

FIELD OF THE INVENTION

The invention relates generally to electronic displays having dual display
5 screens used with computers and CAD design equipment, and more particularly
to various embodiments of an LCD display system permitting positioning of two
or more LCD display screens in a variety of orientations.

BACKGROUND OF THE INVENTION

Computers are readily adapted to operate multiple displays. Paired
10 monitors and screens are useful when large amounts of related information, such
as data or graphics, must be compared. Paired monitors can be inconvenient,
however, where limited desk space is available. Monitors may be horizontally
aligned, or vertically aligned. It is especially desirable to permit swinging of the
monitor orientations together into a "booking" mode.

15 The invention also relates to a novel swingable mounting, which is suitable
for mounting a variety of different pieces of equipment and instruments particularly
for example video cameras, telescopes, mirrors, and any number of different
articles, which it may be desired to swing into a position from which the article is
not easily displaced.

20 The invention also relates to an interchangeable computer display screen,
in which one or more of a variety of screen configurations can be connected or
disconnected in various configurations with a computer.

BRIEF SUMMARY OF THE INVENTION

In one aspect, the invention provides a display system having two screens
25 and comprising a base, a pair of electronic displays mounted on the base and
means for swingably mounting the display screens, for swinging towards one
another for convenient viewing. The swinging means includes an arm assembly

which supports the display screens on the base. The support for the arm assembly from the base may have an orientation relative to the base in which the display screens are positioned in vertically stacked screen relationship and may also have a different orientation in which the display screens are positioned in a horizontal, side by side relationship. Each display screen has a swingable joint connecting it to the arm assembly to permit adjustment of its angular orientation relative to the other screen. The angular orientation of each of the display screens relative to the arm assembly can thus be set by the user so as to orient each display screen in the desired angular orientation for that operator.

10 In one implementation of the invention, the arm assembly can be set in one position about a generally horizontal axis relative to the base, and the display screens can be swung together relative to the arm assembly. The arm assembly may be locked in either orientations, typically vertical or horizontal. Each display screen may be permitted to swing only between a pair of angular positions relative to the arm assembly by controls in the swingable joints.

15 The displays will often be horizontally arranged side by side in their operative angular orientation. It will generally be desirable to minimize the spacing between edges of the display screens whether vertically registered or horizontally registered. To that end, the center-to-center spacing between the display screens is preferably reduced when the screens are swung together.

20 The swingable mounting joints connecting the display screens to the arm assembly are preferably formed in such a way that they can be preconfigured either for a side by side orientation or for a vertically stacked orientation of the screens, with means being provided on the swingable joints to guide the assembly in one fashion or the other, and the arm assembly is preferably provided with connecting means connecting to the swingable joints, which cooperate with the means guiding the assembly.

25 The swingable joints are preferably provided with control abutments by means of which the swinging of the displays can be guided and controlled both when in their horizontal side-by-side arrangement and when in their vertically stacked arrangement, and the position and angular displacement of the two screens can be preset by adjustment of such positional controls during assembly.

A further feature of the invention is the provision of a unique form of spring-loaded pivot mount for mounting equipment, such as the display screen. The pivot mount is capable of adjusting the spring pressure on the pivot so that the article mounted on the pivot mount, in this case a screen can be
5 adjusted, when grasped with both hands and moved, but which is otherwise highly resistant to movement due to frictional locking of the pivot mount.

The pivot mount has numerous other uses, other than mounting display screens as will be apparent from the following description.

Further aspects of the invention provide for the interchangeability of
10 screens one with the other, so that larger or smaller screens may be used with the same computer, and so that screens may be used in various different positions.

In some cases the screens may simply be stood on a table. In other cases the screens may be wall-mounted or mounted on some form of base separate from the computer. In other cases the screens may be interchangeably and
15 releasably mountable for example in a vehicle, and they may be configured in pairs so that they may be portable and set up for a multi screen display, for example, for viewing by a number of persons simultaneously.

The various features of novelty which characterize the invention are pointed out with more particularity in the claims annexed to and forming a part of this
20 disclosure. For a better understanding of the invention, its operating advantages and specific objects attained by its use, reference should be made to the accompanying drawings and descriptive matter in which there are illustrated and described preferred embodiments of the invention.

IN THE DRAWINGS

25 The various advantages of the present invention will become apparent to one skilled in the art by reading the following specification and subjoined claims and by referencing the following drawings in which:

Figure 1 is a perspective illustration of a dual display screen system, showing swinging movement of the two screens towards one another;

30 Figure 2 is a side-elevation of Figure 1;

Figure 3 is a front-elevation of the dual display screens of Figure 1;

Figure 4 is a top plan view of the dual display screens of Figure 1;

Figure 5 is a perspective illustration of dual display screen shown with the screens in vertical arrangement one above the other;

Figure 6 is a side-elevation of Figure 5 showing the screens tilted towards one another;

5 Figure 7 is an exploded view of the pivot mount and ball joint used in this embodiment of the invention;

Figure 8 is a section along the line 8-8 of Figure 7;

Figure 9 is a section along the line 9-9 of Figure 7;

10 Figure 10 is an exploded perspective illustration of an arm assembly, and showing cut away portions of the swingable joints;

Figure 11 is a section along the line 11-11 of figure 10, showing the two components assembled;

Figure 12 is a section along the line 12-12 of Figure 10 showing the two parts assembled;

15 Figure 13 is a perspective partly exploded illustration showing an alternative interchangeable mounting system for mounting the screens;

Figure 14 is an exploded rear perspective illustration of a complementary portion of the mounting system, which is fitted to the back of each screen;

20 Figure 15 is an exploded perspective illustration showing the interchangeable mounting system of the invention coupled with a ball joint similar to that shown in Figure 12, to enable a screen to be mounted on a stand separately from the computer;

Figure 16 is a rear elevation of the complementary portion of the interchangeable mounting system mounted on the back of a screen;

25 Figure 17 is a section along the line 17-17 of Figure 16;

Figure 18 is a perspective illustration partly in phantom of a modified form of stand for a computer screen;

Figure 19 is a perspective illustration of a stand somewhat similar to Figure 18, with a collapsible stand arm nesting in a base;

30 Figure 19a is a perspective of the unit of Figure 19 folded and nested for storage or carrying;

Figure 20 is a rear perspective illustration partly exploded showing a

modified form of computer together with a display releasible mounted on an arm extending from the computer;

Figure 21 is a front perspective illustration of a wall-mounted form of interchangeable display screen together with a control panel;

5 Figure 22 is a schematic illustration showing an interchangeable mounting of a display screen in a vehicle;

Figure 23 is an illustration of another vehicle mounting of the interchangeable displays screen, in the rear compartment of the vehicle;

10 Figure 24 is an illustration of a computer with a rear mounted support arm, and a greatly enlarged display screen fitted to the arm;

Figure 25 is a perspective illustration of a table-mounted screen;

Figure 26 shows a computer having two screens mounted one above the other, with a rotatable mount between the two screens;

15 Figure 27 is a view of the same computer as shown in Figure 26 showing the two screens folded outwardly, so that the display can be viewed by two persons sitting opposite one another;

Figure 28 is an illustration of a portable dual display screen with a hinging mount, the two screens being shown folded together in a stored or carrying position;

20 Figure 29 is a perspective illustration showing a plurality of the display screens of Figure 28 opened up so that they may stand on the table and face in opposite directions, and coupled to a computer;

25 Figure 30 is a perspective illustration of an alternate form of tripod display stand for holding three displays for example, on a conference room table or the like;

Figure 31 is a perspective illustration of the tripod support of Figure 30;

Figure 32 is a rear perspective partially exploded view of another form of dismountable display leg for a display screen;

30 Figure 33 is a rear perspective illustration of a typical lap top computer, having two display screens, the one being slidable relative to the other for nesting, or extendable for use;

Figure 34 is a perspective illustration of the lap top computer with dual

display screens of Figure 33 showing the display screens in another configuration;

Figure 35 is a perspective illustration of another form of lap top computer having two display screens, and showing a slidable cover panel for one of the two display screens;

5 Figure 36 is a rear perspective view of another form of display screen, showing attachment recesses for various components;

Figure 37 is a perspective illustration of, for example, a lap top computer showing two display screens such as that illustrated in Figure 36, being attachable to a hinge mounting on the computer;

10 Figure 38 is a front elevational view of a pair of display screens as illustrated in Figure 36 shown side by side;

Figure 39 is a front elevational view corresponding to Figure 38, but showing the two display screens one above the other;

15 Figure 40 shows an illustration of a further embodiment of invention with a computer having two display screens joined along the side by a hinge;

Figure 41 shows the computer of Figure 40 with the two display screens swung out side by side;

Figure 42 shows the same computer with the two screens swung back to back, so as to display in opposite directions;

20 Figure 43 is a perspective view of a laptop computer system incorporating a center LCD panel and a pair of half-width LCD panels on each side thereof, wherein the half-width panels may be folded over the center LCD panel and the entire display portion then folded down onto the keyboard portion of the laptop to form a compact assembly;

25 Figure 43A is a perspective view of a laptop computer which forms a multimedia center, and which incorporates a pair of foldable speakers flanking a lower LCD screen, and an upper LCD screen hingedly attached to the lower screen;

30 Figure 44 is a side elevational view of a display system of the present invention incorporating a telescoping and pivoting upper support arm for positioning an upper LCD panel adjustably at a desired height above a lower LCD panel or in an orientation facing away from the lower LCD panel;

Figure 45 is a side elevational view of the display system of Figure 44 showing the upper support arm in an extended position;

Figure 46 is a side elevational view of the display system with the upper LCD panel adjusted at an angle relative to the lower LCD panel;

5 Figure 47 is a side elevational view of the display system with the upper LCD panel folded over backward relative to the lower LCD panel;

Figure 48 is a perspective view of the display system in use at an airline ticket counter;

10 Figure 49 is a perspective view of the display system in a folded orientation for easy handling;

Figure 50 is a perspective view of an alternative preferred embodiment of a display system of the present invention incorporating a rotating support member to enable a LCD panel to be rotated about a vertical axis;

15 Figure 51 is a perspective view illustrating an upper LCD panel mounted for swiveling movement relative to a lower LCD panel using the system shown in Figure 50;

Figure 52 is a perspective view of the display system shown in Figure 51 showing the two LCD panels facing in opposite directions;

20 Figure 53 is an exploded perspective view of a modular, multi-panel LCD display system in accordance with another alternative preferred embodiment of the present invention;

Figure 54 is a perspective view of the display system shown in Figure 53 in assembled form ready to accept four LCD panels;

25 Figure 55 is a front view of the display system of Figure 54 with four LCD panels attached thereto;

Figure 56 is a rear view of the display system of Figure 55;

Figure 57 is a perspective view of the display system of Figure 55;

30 Figure 58 is an exploded perspective view of the system shown in Figure 53 but without one of the support arms such that a three LCD panel display system is formed;

Figure 59 is an exploded perspective view of the display system shown in Figure 58 illustrating how a single LCD panel is attached at an uppermost end of

one of the support arms;

Figure 60 is a front elevational view of three LCD panels supported on the display system shown in Figure 59;

Figure 61 is a front elevational view of three LCD panels being supported
5 such that the single LCD panel is below an upper pair of LCD panels;

Figure 62 is a perspective view of a base assembly for supporting three LCD panels in the configuration shown in Figure 62;

Figure 63 is a front elevational view of a four LCD panel system with two of the panels disposed in portrait orientation and two disposed in landscape
10 orientation; and

Figure 64 is a front elevational view of a three LCD panel system with two LCD panels disposed in a landscape orientation and one in a portrait orientation.

Figures 65-67 illustrate perspective views of a display support system in accordance with one preferred embodiment of the present invention;

15 Figures 68-70 illustrate the display support system of Figures 65-67 supporting a pair of LCD screens in various orientations;

Figures 71-74 illustrate perspective views of an alternative preferred embodiment of the display support system of Figures 65-67, which incorporates a screen centering device for centering a pair of LCD screens on a support arm
20 of the system;

Figure 75 is a perspective view of the centering member of the system of Figure 71;

Figure 76 is a front elevational view of the display support system of Figures 71-74 supporting a pair of LCD screens of different dimensions;

25 Figure 77 is a partial plan view of the display screen support system shown in Figure 71 illustrating the limited degree of booking available because of limited clearance between the edges of the LCD screens and the support arm of the system;

Figure 78 is a partial plan view of an alternative preferred embodiment of a display screen support system which allows for an increased degree of booking
30 of two LCD screens by virtue of a concavity formed in a support arm portion thereof;

Figures 79 and 80 are perspective views of the display support system of Figure 78 but with a base assembly incorporating extendable foot portions to increase the effective footprint of the base assembly;

Figure 81 is a perspective view of the base assembly of Figures 79 and 80
5 but with an increased base panel portion to provide even further stability to the base assembly;

Figures 82 is a perspective view of a mechanism for enabling smooth extending movement of each of the arm members of the display support system shown in Figures 71-74;

10 Figure 83 is a perspective view of an alternative preferred mechanism for enabling smooth rolling movement of the support arms within a common support member;

Figure 84 is a perspective view of another alternative preferred form of the arm member incorporating semi-circular grooves and channels for smooth sliding
15 movement of the arm members;

Figure 85 is a perspective view of an alternative preferred embodiment of the arm member of Figure 84 illustrating the use of square shaped channels and shoulder portions;

Figures 86-88 are perspective views of a display support system which
20 enables an LCD screen mount to be quickly repositioned in either a portrait or a landscape orientation;

Figure 89 is a partial cross sectional view in accordance with section line 89-89 in Figure 88;

Figure 90 is a partial cross sectional view of an alternative preferred
25 embodiment of the display system shown in Figure 89, which incorporates stop members for limiting movement of an LCD mount member between two positions 90 degrees apart from one another;

Figure 91 is a simplified cross sectional view of the neck portion of an LCD support member in accordance with section line 91-91 in Figure 90 illustrating the
30 two grooves which limit movement of the neck portion;

Figure 92 is a perspective view of the LCD screen mounting member and a portion of the support member, illustrating the recess in the support member;

Figures 93-103 are perspective views of an LCD display system incorporating a universal ball joint hinge for enabling a pair of LCD screens to be placed in various orientations;

5 Figures 104 and 105 are elevational views of an arrangement for positioning two LCD screens on a common support arm such that the screens can be repositioned in either portrait or landscape orientations without requiring same to be spaced at different distances from one another;

 Figure 106 is a perspective view of a release member in accordance with an alternative preferred embodiment of the invention;

10 Figure 107 is a partial side view of the release member of Figure 107;

 Figure 108 is an end view of the release member taken in accordance with directional arrow 108-108 in Figure 107;

 Figures 109-111 are perspective views of the release member being inserted into an associated support member;

15 Figures 112-114 are perspective views of the release member being rotated within the opening in the support member;

 Figure 115 is a perspective view of a portion of the support member of Figures 104-114;

20 Figure 116 is a front view of a portion of the support member showing the opening therein in greater detail;

 Figure 117 is a partial cross sectional view illustrating the release member in one orientation within the opening in the support member;

 Figure 118 is a partial cross sectional view of the release member having been moved 90 degrees counterclockwise from the position shown in Figure 117;

25 Figure 119 is a partial cross sectional side view of the release member coupled to a lever assembly associated with the support member, with the lever assembly locking the camming member in place relative to the support member;

30 Figure 120 illustrates the lever assembly shown in Figure 119 in an unlocked orientation, thereby enabling rotational movement of the release member;

 Figure 121 is a perspective view of the support member and lever assembly shown in Figure 119, with the lever thereof in the locked position;

Figure 122 is a view of the lever of Figure 121 but with the lever in the open position;

Figure 123 is an alternative preferred embodiment of an arm assembly of the present invention incorporating a threaded locking member for locking the arm member relative to an associated support member;

Figure 124 is an enlarged perspective view of a portion of the arm member within the support arm, and with the support member shown in phantom;

Figure 125 is a partial end cross sectional view taken in accordance with section line 125-125 in Figure 123;

Figure 126 is a partial cross sectional view taken in accordance with section line 126-126 in Figure 125;

Figure 127 is an alternative preferred embodiment of the present invention substantially in accordance with the embodiment of Figures 123-126 except for the inclusion of a plurality of rollers to assist in providing smooth rolling movement;

Figure 128 is an exploded perspective view of an alternative preferred embodiment of the present invention incorporating a ball joint assembly adapted to be easily adjusted to four different positions on a support member;

Figure 129 is a perspective view of the mounting block shown in Figure 128;

Figure 130 is an assembled side cross sectional view of the assembly shown in Figure 128;

Figures 131-133 illustrate dimensional considerations for mounting two LCD screens such that various edges of each align with each other when the two screens are in different orientations;

Figure 140 is a front view of a dual LCD screen monitor system having one screen rotating into a portrait mode;

Figure 141 is a top view of the display system of Figure 140 illustrating the outwardly booked position of the rightmost LCD screen during rotation thereof;

Figure 142 is a front view of the display system of Figure 140 but with the leftmost LCD screen booked outwardly to enable rotation thereof;

Figure 143 is a plan view of the display system of Figure 142;

Figure 144 is a front view of the display system of Figure 142 in the

process of being rotated clockwise while in an outwardly booked position;

Figure 145 is a plan view of the display system of Figure 144;

Figure 146 is a front view of the display system of Figure 144 with both LCD screens rotated completely into a portrait mode;

5 Figure 147 is a plan view of the display system of Figure 146;

Figure 148 is a partial cross-sectional view in accordance with section line 148-148 in Figure 147 of the ball joint assembly of Figure 134 in use with the leftmost LCD screen in Figure 147;

10 Figure 149 is a cross sectional view in accordance with section line 149-149 of Figure 147 of the ball joint assembly in use with the rightmost LCD screen in Figure 147;

Figure 150 is a perspective view of a portion of a base assembly for an LCD display system incorporating a built in control panel;

15 Figure 151 is an enlarged perspective view of the control panel shown in Figure 150;

Figure 152 is a perspective view of a display system incorporating a flexible camera mounted in a support arm thereof;

Figure 153 is a perspective view of an alternative preferred embodiment of the camera of Figure 152 but also including a microphone integrated therewith;

20 Figure 154 is a front view of the display system of Figure 152 including a pair of LCD screens attached thereto;

Figure 155 is a side view of the display system of Figure 155;

Figure 156 is an enlarged perspective view of the camera shown in Figure 152;

25 Figure 157 is a front view of an alternative preferred embodiment of an LCD display system incorporating a camera built into the bezel of one of the LCD screens thereof;

Figure 158 is a perspective view of a clip incorporating a camera which can be secured to a bezel of an LCD screen; and

30 Figure 159 is a partial perspective view of an LCD screen incorporating the clip attached to the bezel of the screen.

DESCRIPTION OF A SPECIFIC EMBODIMENT

As already explained, the invention in this particular embodiment illustrated, has its application to the use of dual display screens, which can be used to display two different computer images simultaneously. This may have application for example in CAD computer design application. For these and other purposes it is particularly useful if the two screens or displays can be tilted towards one another so that they appear in the form more or less of two pages of an open book. The screens are preferably arranged side by side, in horizontal alignment, but may also be arranged vertically one above the other.

Referring now to Figures 1, 2 and 3, the invention is there illustrated as in the form of a pair of video display screens 10 and 12, each of which may be of known construction, but which may typically be liquid crystal displays for example. They are each provided with video terminal connectors 14 (Figure 2) by means of which they may be connected to a computer.

Each of the screens 10 and 12 comprises a central rectangular display portion 16, and a rectangular marginal frame 18.

The two display screens 10 and 12 are mounted at opposite ends of a mounting arm 20. The mounting arm 20 is itself supported on an upright stand 22 and a base 24. The arm 20 may be connected to the base 22 by a coupling means 26 (Figure 4) by means of which the arm may be attached during assembly, either horizontally, or vertically (Figure 6) prior to delivery to the customer.

In some cases the manufacturer may simply make the arm permanently attached in one position, i.e. horizontal or the other i.e. vertical, to reduce expense.

As will be noted in Figures 2 and 4, each of the displays 10 and 12 is mounted on respective free ends of arm 20, by means of a swingable mounting means 28 and 30 respectively.

The swingable mounting means 28 and 30 are so constructed as to permit the two screens 10 and 12 to be swung together towards one another, into the

configuration shown in Figures 1 and 4, in which they both remain in the same upright planes, and in which they are both swung towards one another by equal angles. In this way, as the two screens 10 and 12 are swung towards one another into this configuration, the angular displacement of one screen is equal
5 to the angular displacement of the other screen, so that the two frames 18 of the screens 10 and 12 substantially meet at a central point indicated generally as P, thus bringing the two screens 16-16 as close as possible together and at the same time, as far as possible, simulating the appearance of two pages of a book opened up.

10 It will be observed that when the arm 20 is fastened in its vertical position as shown in Figures 5, the lower one of the two screens 10 and 12 is moved up the arm, because in the vertically stacked orientation, the rectangular screens have a shorter vertical dimension, and it is desirable that they should be as close to one another as possible when they are swung together, so that the longer sides
15 meet at point P.

From the foregoing description it will be understood that it is desirable that the two screens can be swung together into their inwardly angled relation as shown in Figures 1 and 4, or Figure 6, but that the screens should be capable of being tilted only to a limited degree in any other direction relative to one another,
20 since this might reduce the clarity of the dual display. However, the two screens may be tilted slightly upwardly, or downwardly by similar angular displacements. In this way the simulation of an open book arrangement is maintained.

For these reasons, the two display screens 10 and 12 are mounted on the arm 20 by means of the swingable mountings 28 and 30. These mountings will
25 now be described in greater detail with regard to Figures 7, 8 and 9.

Figure 7 illustrates the mounting 28 or 30 in an exploded perspective view. The swingable joint consists essentially of a ball 32, and a socket 34, with the ball 32 being preferably cast out of a suitable material preferably a metallic material and the socket 34 being cast preferably of a somewhat resilient material such as
30 a thermoplastic. The ball 32 is mounted on a neck 36, which extends from a generally rectangular junction block 38. The block 38 is formed with a plurality, in this case four, rectangular guide members 40, spaced apart at 90 degrees from

one another around the block 38.

One of the guide members 40A, is wider than the other three guide members 40, to provide guidance when the guide members are assembled in a manner to be described below.

5 The block 38 and guide members 40 are designed to fit into suitable recesses in the arm 20 (described below).

A collar member 42 of generally semi-arcuate shape, is designed to fit over the block 38 and around the socket 34, for reasons to be described below. Collar 42 is formed with fastening flanges 44 by means of which it may be secured in
10 position as described below.

In this particular embodiment, the arm 20 is provided at each end with three mounting recesses 46A, 46B and 46C. Each mounting recess 46 has four channel shaped grooves 48 formed therein spaced at ninety degrees therearound. The channel shaped grooves 48 are intended to receive the rectangular guide
15 members 40 of the swingable joints.

One of the guide channel grooves 48A is wider than the others, to receive the wider one 40A of the rectangular guide members. In this way the guide members provide a keying function, which controls the positioning of the swingable joints and the display screen.

20 Bolts 50 align with the blocks 38, and are received in suitable threaded bores 51 (Fig. 7) and secure the assemblies in position.

The ball 32 is provided with a plurality, in this case four screw receiving bores 52, adapted to receive screws 54 therein. The sockets are spaced around the widest part of the ball 32, and are radially spaced apart by 90 degrees from
25 one another. It will be appreciated that while there are four such bores 52, in certain circumstances only two or three screws 54 will be inserted, for reasons to be described below.

The heads of the screws 54 are cylindrical and protrude outwardly from the ball 32, and are received in respective slots 56 formed in socket 34. The ball 32
30 is a snug frictional fit within the interior of socket 34, so that a significant twisting moment is required to rotate the ball within the socket.

Clearly depending on the number of screws 54 in position, the actual

movement of the ball in the socket is restricted. Thus for example if there are three such screws 54 in position, two of the screws 54 will simply limit the movement of the ball 32, so that the ball 32 can virtually be moved only around the axis of the two screws 54. If a third screw 54 is inserted then it will restrict movement of the ball so that it can be rotated only in such a fashion that the screw 54 rides along its respective groove 56, but that it will not be able to move significantly in the reverse angular direction.

For reasons to be described below, two of the slots 56A and 56B are wider and the other two slots 56 are narrower.

The socket 34 has a generally annular base 58, and a spring loaded plate 60 abuts against the annular base 58. The shape of the socket 34 is such that a small cylindrical boss 59 project through a registering opening in the spring plate 60, (Fig. 9).

The spring plate 60 is secured in position by means of screws 62 passing through suitable registering openings 61 on the flange 44 of the collar 42, and secured in threaded openings 63 in plate 60.

By tightening or loosening the screws 62, it is possible to apply greater or lesser pressure by flexing the plate 60 against the rear surface of socket 34, and thus adjust the friction between the surface of the ball 32 in the socket 34. In this way it is possible to preset the rotational force or torque that would be require to rotate the ball in the socket.

Additional control of the friction on the ball is provided by means of the frusto-conical collar 42. This mates with frusto-conical bevels 64 on the exterior of collar 34. Thus by tightening or loosening the screws 50 in the sockets 48, the collar 42 can be made to squeeze and wedge the four sides of the socket 34 together tightly around the ball 32 and thus still further control the friction applied by the socket 34 to the ball 32.

In order to further control and limit the swinging of the ball 32 and stem 36 relative to the socket 34, limiting screws 70-70 are provided, which can be inserted or removed in suitable threaded inserts 72-72 in annular base 58 of socket 34.

One or more such screws 70 can be inserted (Figure 9) and can be adjustably positioned, so as to abut against the cylindrical heads of screws 54, and thus limit swinging of the ball 32.

Access to screws 70 can be obtained through registering opening 74 in
5 plate 60.

As mentioned, all of these settings would be preset in the factory before shipment, so that in use the actual scope of movement of the display screen, by means of rotating the ball 32 in the socket 34 is substantially restricted or limited.

It will thus be seen that the novel ball and socket joint described provides
10 a great degree of control on the angular position of the article attached to it, in this case the screens 10 or 12. In fact, by suitable adjustments in the factory, the friction on the ball 32 can be made sufficiently tight that it is substantially impossible to manually move the arm 36 on which the ball 32 is mounted, simply by grasping the block 38.

15 However, the friction can be so adjusted that by grasping the two edges of the display screen, the position of the display screen can be manually adjusted to the most suitable position, and once adjusted it will remain substantially fixed in that position.

Thus, once the block 38 is inserted in position in its socket in the arm, and
20 locked in position, then by grasping the two side frames of the screen, sufficient torque can be applied, to adjust the position of the screen and rotate the ball 32 in the socket 34 until the screen is in the desired position.

In accordance with various further embodiments of the invention as illustrated in Figures 13 through 29, the invention provides for a still greater range
25 of interchangeability either as between one screen and another screen for computer, which may facilitate either the use of a small portable screen or a much larger screen, or the use of a plurality of screens, or the ready interchangeability of simple forms of screen mountings.

Figures 13, 14, 15 and 16 indicate one form of interchangeable screen
30 attachment, being a further embodiment of the ball and socket joint as illustrated in Figures 7 through 12. In this further embodiment, a modified form of plate 80 is secured to the ball and socket joint 28-30. The plate 8 in this case is formed

with a generally V-shaped socket 82, the edges of the V-shaped socket being formed with flanges. A complementary attachment plug 84 is mounted on a plate 86 which is secured to the back of the screen 18. In this embodiment the arm 20 is shown mounted on an independent base stand 88, and the actual computer and keyboard may be located elsewhere and simply connected by suitable coupling cables (not shown) so that the entire arrangement of displays and mounting arm can be positioned wherever it is most convenient.

In this embodiment, for added security, locking screws 90 may be provided in either side of the V-shaped recess 82. The flexibility of the interchangeable screen system according to the invention is further illustrated in Figures 18 and 19. In this case, a portable mounting base for a single display screen may be provided. In this case a base 92 is formed with a groove 94. A swingable upright arm 96 is swingable into and out of the groove 94. The arm 26 may have a telescopic ability, and may be provided with a V-shaped retaining slot 98 at its upper end, for retaining a display screen shown in phantom as 12, having a mounting plug 84 formed to fit the slot 98. If desired the slot 94 may also be arranged to hold a manual computer "mouse" device of a type well known in computer art indicated generally as M, giving a limited degree of control over the display on the screen. Figure 19a illustrates the device with the arm 94 swung downwardly into the groove 92 and nested.

Figure 20 illustrates a modification of this concept, in which for example a computer of the lap-top type indicated generally as C may be provided with a swingable support arm 100, having a V-shaped slot 102 at its upper end similar to the slot 98. A display screen indicated generally as 12 may have a mating groove or recess 104 adapted to receive the arm 100, and within the groove 104 there is a V-shaped locking flange 106 shaped to mate with the V-shaped slot 102. The locking flange 106 can be provided with electrical contacts 107. Contacts 107 can be arranged to contact matching contacts 108 (Fig 19), in the V shaped slot 102. This arrangement can be used in all these embodiments to avoid the use of cables wherever possible.

In this way the entire combination of lap-top computer and display 12 can be fitted together and swung down into a closed position for carrying or storage

and can be swung upwardly for use, and if desired, the screen 12 as illustrated can be easily removed and a screen having different characteristics or a larger screen can simply be snapped in position, if desired.

Figure 21 illustrates the adaptability of the system for use in for example
5 the removable mounting of a display screen on a wall, or the side of a booth for example. In this case a wall mounting block 110 can be attached by any suitable fastening means (not shown) for securing the same to a vertical surface. The mounting block 110 may have finger operated controls similar to a computer
10 "Mouse" for limited control of the display on the screen for demonstration or presentation purposes and may have speakers for combined audio and visual effects.

The display screen 12 itself can again simply be mounted on an upright arm 112 having at its upper end a generally V-shaped recessed body 114, preferably on a hinged mount 116. The screen 12 will be supplied with a suitable
15 V-shaped locking flange on its rear surface (not shown) of the type already described.

Figure 22 illustrates the same concept for the mounting of a display screen indicated as 12 in a vehicle. This may have application particularly for sales persons and for displaying maps of cities and the like, to assist drivers of delivery
20 vehicles. In this case the display screen 12 can be mounted on an arm 120 secured at a suitable position on the front of the interior compartment of the vehicle. Again a releasable mount of the V-shaped slotted type shown as 122 is provided on the arm 120, and the screen 12 would be provided on its rear with a suitable inverted V-shaped locking flange fitting in the recess 122. There would
25 also be provided matching electrical contacts, described above, in these components, to avoid the use of cables. In this way, the screen 12 could be placed and locked in position when it was required, and when the vehicle was parked the screen 122 could simply be easily dismounted and placed in the trunk, or taken out of the vehicle altogether, for greater security.

30 The screen 12 would be connected to a suitable small computer (not shown) again being of the portable type so that it could readily be removed from the vehicle.

A somewhat similar arrangement could be made for the rear compartment of the vehicle illustrated in Figure 23. In this case a swingable arm 126 is shown mounted in the rear surface of each of the front seats indicated as S in a vehicle.

5 A suitable V-shaped slotted mounting recess 128 would be mounted on the arm 126. The arm 126 could be swung out from the seat, and a display screen 12 could be mounted on the V-shaped recess.

10 Figure 24 illustrates a typical laptop computer C, having an enlarged display screen 12 mounted on a hinged arm 130, which is hinged to the rear of the computer. This illustrates the adaptability of the interchangeable screen mounting using the V-shaped recess and plug, so as to adapt a smaller laptop type computer C, with use with a much larger screen 12.

15 Figure 25 illustrates the use of a free-standing screen 12 having a rearwardly mounted hinged leg 132, which can be swung rearwardly to support the screen at an angle somewhat in the manner of an easel. Again, the hinging leg 132 can be connected to the back of the screen 12 by interchangeable means such as the V-shaped recess and plug, if desired.

20 Figure 26 illustrates another configuration, in which a computer indicated generally as C may be provided with two screens 12A and 12B swingably and hingeably mounted to the rear edge of the computer C. The lower screen 12A is hinged along the line 134. The upper screen 12B is hinged to the lower screen 12A by means of the generally cylindrical tubular hinge bar 136.

25 As illustrated in Figure 27, the uppermost screen 12B can be swung into an obtuse angle relative to the lower screen 12A so that the two screens 12A and 12B can be viewed by at least two persons sitting opposite to one another. By means of suitable software, when the upper screen 12B is swung into the obtuse angle shown, the image on the screen 12B will be reversed, so that the images on screens 12A and 12B are both viewed the right way up.

Figures 28 and 29 illustrate forms of free-standing dual screens indicated generally as 140 and 142, connected together by a tubular hinge bar 144.

30 The pairs of screens 140 and 142 can be swung open at obtuse angles to one another and stood on a surface such as a table as illustrated in Figure 29. They may be connected to a computer C by means of daisy chain cables 146,

which plug into opposite ends of the tubular hinge bar 144. As in the embodiment of Figures 26 and 27, the computer will contain suitable software the nature of which is to invert the image as between one screen and the other so that both screens show their respective images the right way up.

5 Various other modifications and adaptations can also be made using the principles of the invention.

Thus, Figure 30 is a perspective illustration of an alternate form of tripod display stand 145 for holding three displays 12 for example, on a conference room table or the like.

10 Figure 31 is a perspective illustration of the tripod support 145 of Figure 30.

Figure 32 is a rear perspective partially exploded view of another form of dismountable display leg 130 for a display screen 12.

Figure 33 is a rear perspective illustration of a typical lap top computer C, having two display screens 12A and 12B, the one being slidable relative to the
15 other for nesting, or extendable for use on arms 150.

Figure 34 is a perspective illustration of the lap top computer C with dual display screens 12A and 12B of Figure 33 showing the display screens in another configuration.

Figure 35 is a perspective illustration of another form of lap top computer
20 C having two display screens 12A and 12B, and showing a slidable cover panel 152 for one of the two display screens.

Figure 36 is a rear perspective view of another form of display screen 154, showing attachment recesses 156 for various components. Electrical connections 157 are incorporated in the recesses 156 for interconnection with matching
25 contacts (not shown) in suitable accessories. Accessories may include audio speakers, and video cameras for direct feed back, to give only two examples.

Figure 37 is a perspective illustration of, for example, a lap top computer C showing two display screens 154-154 such as that illustrated in Figure 36, being attachable to a hinge mounting 158 on the computer.

30 Figure 38 is a front elevational view of a pair of display screens 154-154 as illustrated in Figure 36 shown side by side with audio speakers 158 and video cameras 159 attached.

Figure 39 is a front elevational view corresponding to Figure 38, but showing the two display screens 154-154 one above the other,

As best shown in Figures 40, 41 and 42, a further embodiment of the invention may provide for a typical computer C having two display screens 160
5 and 162. The screen 160 is hinged to the computer by means of a hinge 164. The second screen 162 is hinged to the first screen by means of a vertical hinge along one side indicated as 166.

As best shown in Figures 41 and 42, the two screens 160 and 162 may either be swung out so that they are side by side with one another facing the
10 operator of the computer C, or, as shown in Figure 42, the two screens may be swung so that screen 162 is back to back with screen 160, thereby displaying the display both to the operator of the computer and to somebody sitting facing him. In this form of the invention special software and the like will not be required for the reversing of the images, since both images will be shown the right way up.

Referring briefly now to Figure 43, a computer 168 in accordance with
15 another alternative preferred embodiment of the present invention is shown. The computer incorporates a center LCD panel 170 pivotably mounted by a hinge 172 to a base portion 174 of the computer. Pivotably supported on opposite sides of the center LCD panel 170 are a pair of LCD panels 176 which are each about
20 one-half the width of the center LCD panel 170. The outer LCD panels 176 are supported by hinges 178, which may be identical in construction to hinge 172. The outer LCD panels 176 may be folded over the center LCD panel 170 and the entire display portion comprising panels 170 and 176 then folded down against the base 174 to form a compact unit that may be easily carried.

In Figure 43A, a multimedia laptop computer 168' is shown. The computer
25 168' incorporates a pair of speakers 175 which are hingedly coupled via hinges 178' to a lower LCD panel 170'. The lower LCD panel 170' is itself hingedly coupled to a keyboard portion 174' via a hinge 172'. An upper LCD panel 179 is also hingedly coupled via a hinge 177 to the lower LCD panel 170'. When folded,
30 the computer 168' forms a compact, lightweight system.

Referring now to Figures 44-49, a display system 180 in accordance with another alternative preferred embodiment of the present invention is shown. The

display system 180 includes a base 182 and a support column 184. Secured to the support column 184 is a lower support arm 186 and a telescoping upper support arm 188. Attached to each support arm is a mounting assembly 190, which preferably comprises a ball joint such as that described herein. Secured
5 to each mounting assembly 190 is a LCD panel 192.

With specific reference to Figures 45-47, the lower support arm 186 comprises a tubular construction and the upper support arm 188 comprises a neck portion 194 which enables the upper support arm 188 to be extended (i.e., telescoped) relative to the lower support arm 186. The upper support arm 188
10 further includes a hinge 196 which enables the upper LCD panel 192 to be angled relative to the neck portion 194 so as to place it at a convenient viewing angle. As is apparent in Figure 47, the upper LCD panel 192 can even be rotated into position to face away from the lower LCD panel 192. This orientation is particularly well suited for retail applications where a sales person needs to view
15 information while inputting product or other information, and where it is desirable to display to the customer various items of information as the transaction is conducted. Advantageously, the telescoping upper support arm 188 and the hinge 196 enable the two LCD panels 192 to be placed at separate heights to accommodate airline ticket counters, hotel registration counters and other like
20 structures where an employee's counter is frequently at a different height from a surface or counter useable by a customer.

Figures 47 and 48 illustrate the display system 180 in use at an airline ticket counter 198 having a first counter 200 at a lower height than a second counter 202. In this application it will be appreciated that suitable software will be required
25 to "flip" the image displayed on the upper LCD panel 192. The telescoping upper support arm 188 inherently provides a degree of adjustability to accommodate a range of counter heights without modification to the either of the support arms 186,188 or the support column 184.

Figure 49 illustrates the two LCD panels 192 folded together such that the
30 display system 180 forms a compact assembly which may be easily transported if needed. In this regard it will be appreciated that any form of conventional clasp may be included to secure the folded LCD panels 192 to one another or to the

base. Also, a handle could easily be attached to a portion of the display system 180, such as the support column 184, to enable the system 180 to be easily transported.

Referring now to Figures 50 and 51, still another display system 200 is shown. With specific reference to Figure 50, the display system 200 includes a support column 202 and an upper support member 204 having a neck portion 206. The support column 202 includes a bore 208 adapted to receive the neck portion and enable the neck portion 206 to rotate or swivel therein such that the upper support member 204 can be swiveled. The support member 204 is secured to a rear surface 212 of a LCD panel 210 through either a fixed arrangement or a pivotable mounting arrangement such as disclosed herein. The neck 206 may be captured by any suitable arrangement in the bore 208 such that the LCD panel 210 is not removable from the support column 202. Alternatively, it may be releasably disposed in the bore 208 such that the entire upper support member 204 and LCD panel 210 may be lifted out of the column 202 before repositioning the LCD panel 210 as desired. In this manner the clearance between the LCD panel 210 and the support column 202, which would otherwise be important for allowing the support member 204 to freely rotate with the LCD panel 210 thereon, will not be a concern.

With specific reference to Figure 51, the display system 200 is shown with the upper LCD panel 210 rotated to a position perpendicular to a lower LCD panel 212. The support column 202 is supported on a base 214. In Figure 52 the upper LCD panel 210 is rotated 180 degrees from the lower LCD panel 212 to permit two individuals facing each other to each view one of the LCD panels 210, 212.

Referring now to Figure 53, a modular display system 300 is shown in accordance with another alternative preferred embodiment of the present invention. The display system 300 is intended to support anywhere from one to four independent LCD display panels, but it will be appreciated that the system 300 could easily be expanded to support more than four LCD panels if needed, as will be explained momentarily.

Referring to Figure 53, the system 300 includes a base 302, a support

column 304, a first support arm 306, a second support arm 308 and a third support arm 310. Each support arm 306, 308 and 310 includes at least two coupling assemblies 312, and preferably three such assemblies 312. The support column 304 also includes once such assembly 312, although this member could
5 also include several assemblies 312 if needed. Support arms 306, 308 and 310 each also include a mounting member 314 (with the mounting member of support arm 306 being hidden in Figure 53) which is disposed preferably at an approximate mid-point along a length of its support arm. Each mounting member 314 is adapted to engage in either one of two positions 90 degrees offset from
10 one another in one of the coupling assemblies 312 in a key-like fashion to hold its associated LCD panel in either a portrait orientation or a landscape orientation.

The pair of coupling assemblies closely adjacent each other on each support arms 308 and 310 are provided to space two adjacently positioned LCD panels mounted on each arm slightly farther apart from each other to provide
15 additional clearance needed when the two LCD panels are placed in a landscape orientation. Thus, in a landscape orientation, the two LCD panels supported on either of the arms 308 and/or 310 will be supported at the two outermost coupling assemblies 312 near the very ends of each arm. In a portrait orientation the LCD panels will need to be spaced closer to each other, thus requiring one of the LCD
20 panels to be coupled to the more inwardly positioned assembly 312a (Figure 53) of each support arm 308 and 310. The closely positioned pair of coupling assemblies 312 on support arm 306 enables the third support arm 310 to be mounted in one of two positions on arm 306 depending upon whether the LCD panels are disposed in a landscape or a portrait orientation. Figures 55-57
25 illustrate four LCD panels 316 supported on the display system 300. It will be appreciated that each of the LCD panels 316 includes a mounting member identical or similar to members 314 on a rear housing surface thereof such that each can be quickly and easily coupled to one of the coupling assemblies 312.

It will be appreciated that the display system 300 could easily be used to
30 support less than four LCD panels 316 if desired. For example, in the drawing of Figure 54 the second support arm 308 could be eliminated and the one LCD panel 316 coupled directly to the vertically uppermost coupling assembly 312. This

arrangement is illustrated in Figures 58-60. Alternatively, the lower support arm 310 could be eliminated and a LCD panel 316 coupled directly thereto as illustrated in Figures 61 and 62.

It will be appreciated that the display system 300 could be easily modified through the use of additional support arms to support more than four LCD panels 316 if needed. For example, the support arm 306 could be lengthened sufficiently to extend above the second arm 308, and a fourth support arm identical to arms 308 and 310 could be coupled perpendicularly thereto such that two extra LCD panels could be supported. An even longer support member and still another extra support arm could be incorporated to support eight LCD panels 316. As can be appreciated, a very large plurality of independent LCD panels can be supported from a single base 302 and support column 304 if needed. Particularly desirable is the feature of being able to orientate the LCD panels 316 in either portrait or landscape mode, or a combination of each, as needed. Figures 63 and 64 illustrate variations of the above described display systems incorporating both landscape and portrait orientated LCD panels 316.

Referring now to Figures 65-70, a display system 400 in accordance with another preferred alternative embodiment of the present invention is illustrated. Display system 400 incorporates a base assembly 402, a vertical support member 404, and a pair of telescopically mounted support arms 406 supported by a central arm 408 which is secured to the vertical support member 404 either fixedly (i.e., non-movably) or for rotational movement relative to the vertical support member 404. Each support arm 406 includes a mounting member 410 for supporting an LCD screen on the arm, as hereinbefore described. The support member 408 may be tubular, in the form of a C-channel or the form of a U-channel, and telescopically supports each arm 406 for sliding movement into or outwardly of the support member 408. Since the two support arms 406 are independent members, each can be extended or retracted without the need for moving the other support arm 406.

With specific reference to Figures 65 and 68, the system 400 is shown supporting a pair of LCD screens 412 attached to the mounting members 410 both in a portrait orientation. In this illustration, the LCD screens 412 comprise 10 inch

screens. The independent adjustability of each support arm 406 enables each LCD panel 412 to be extended to the position needed to place the two LCD screens 412 closely adjacent each other.

Referring to Figures 67 and 70, the display system 400 is shown supporting
5 one of the LCD display screens 412, which in this example is a 10 inch screen, in a portrait orientation, and the other screen 412, which in this example is a 15 inch screen, in the landscape orientation. The independent movement of each support arm 406 allows each to be adjusted to the proper length of extension to permit the LCD screens 412 to be positioned side-by-side in this orientation, and
10 also such that they are abutting or virtually abutting each other so that there is no objectionable gap between them. The display system 400 thus enables monitors of varying sizes to be mixed as needed and positioned to most efficiently enable the user to view information on the screens 412.

Referring now to Figures 71-75, a display system 500 is illustrated in
15 accordance with another alternative preferred embodiment. The system 500 is identical to the system 400 of Figures 65-67 with the exceptions of locking mechanisms on each of the support arms and a centering device for centering two LCD screens on the display system 500.

Referring specifically to Figure 71, the display system 500 includes a base
20 502, a vertical support member 504 fixedly secured to the base 502, and a pair of support arms 506 each disposed for telescopic movement relative to a center support arm 508. The center support arm 508 also includes two locking mechanisms 510 which can be used to lock each support arm 506 at a desired position such that the locked arms 506 cannot move. A centering member 512
25 is pivotably disposed on the support arm 508.

The locking mechanisms 510 may comprise buttons which are biased toward their respective support arm 506 such that they automatically engage with preformed openings in their respective support arm 506, and need to be depressed to release their associated support arms before each can be extended
30 or retracted from the support member 508. Figure 72 illustrates the support arms 506 in their fully retracted positions.

Referring to Figures 72-76, the centering member 512 will be described in

further detail. The centering member 512 comprises an independent member which is pivotably secured by a pair of pivot pins 514, shown in Figure 75, which are disposed in openings formed in the support member 508. When in the retracted or closed position shown in Figure 72, the centering member 514 sits
5 flush with an outer surface of the support member 508. When extended, the centering member 514 projects outwardly of the support member 508 to form a means by which the LCD screens supported on the arms 506 can be precisely centered on the arm 508. In the retracted position, the centering member 514 rests within a recess or opening 516 formed in the arm 508. Figure 74 shows the
10 centering member 512 extended to enable centering of a pair of LCD screens 518 mounted thereon via mounting members 520. Figure 76 illustrates a pair of LCD screens 518 of different sizes to further illustrate the easy centering thereof by use of the centering member 512.

Referring now to Figure 78, a means of providing enough clearance around
15 the support arm of a display system to permit increased booking of a pair of LCD screens is shown. In Figure 77, a display system 600 substantially identical to the display system 400 of Figures 65-67 is shown, illustrating that this system enables a slight degree of booking which, in some situations may not be as much as a user would desire. In this example each LCD screen 612 can only be "booked"
20 inwardly toward each other a slight degree due to the presence of the support arm 608. The display system 700 shown in Figure 78 overcomes this problem. The display system 700 includes a vertical support member 704 which supports a support member 708. The support member 708 telescopically supports a pair of independent support arms 706. However, the support member 708 is formed with
25 a concavity or "bend" 708a at the longitudinal midpoint thereof. The centering component 714 is preferably disposed at this midpoint 708a and may include an arcuate shape to conform and blend in with the outer surface of the support member 708 at this point on the member 708. Thus, an increased degree of booking is enabled without the requirement of any additional component parts.

30 Referring to Figures 79-81, a display system 800 in accordance with another alternative preferred embodiment of the present invention is shown. The display system 800 includes a modified base assembly which can be adjusted to

provide a larger "effective" footprint to thereby support larger LCD screens with even greater stability.

The display system 800 includes a base 802, a vertical support member 804, and an arm assembly 806 which, in this embodiment, is identical to the arm construction of the embodiment 700 shown in Figure 78 and the description above relating thereto. It will be appreciated immediately, however, that the base assembly 802 could be used with virtually any form of arm, and is therefore not limited to the support arm 806 shown in Figure 79.

The base assembly 802 includes a platform 808 which includes at least a pair of integrally formed channels 810. Each channel telescopically supports an independent support foot 812. Each support foot 812 includes a neck portion 814, illustrated in Figure 80, which resides completely within its associated channel 810 when the foot is in a retracted position, as illustrated in Figure 79.

When one or more LCD screens are being supported on the arm assembly 806 which, because of their size or weight, require a larger support "footprint" to ensure stability thereof, the foot portions 810 can be quickly and easily extended by simply pulling outwardly on each. This provides a larger effective footprint for the base 802 and therefore even greater stability. When the larger footprint is not required, the foot portions 810 can simply be pushed into the channels 810 to shrink the footprint such that the base 802 takes up less space on a desk, credenza, etc. Advantageously, no tools are required to enlarge the footprint of the base 802 and any LCD screens mounted on the display system 800 do not need to be removed before extending the foot portions 812.

Referring now to Figure 81, a modified base 802a is shown which includes an even larger platform 808 made up by a larger front base portion 803 is shown. Base 802a enables an even further degree of stability to be achieved over the embodiment of the base 802 shown in Figure 79.

Referring now to Figures 82-86, various embodiments are disclosed for enabling smooth, sliding movement of the support arms described in connection with Figures 65, 71 and 78. In Figure 82, a support arm 900 and a support member 910 are illustrated. The support arm 900 has a neck portion 902 and an end portion 901. The end portion 901 includes an LCD screen mount 901 such

as described hereinbefore.

The neck portion 902 includes a pair of rollers 904 mounted for free rolling movement and such that they extend just slightly beyond the outer upper surface 902a of the neck portion 902. Optionally, the neck portion 902 can include a
5 channel 906 formed in one or a pair of opposing side wall portions 908 of the neck portion 902. A center support member 910 is formed of a tubular construction and includes a projecting lip portion 912a extending from a lower wall 912. Disposed in the lower wall 912 are a pair of rollers 914 mounted for rotation in cut-outs 916. The interior area of the support member 910 accepts the neck
10 portion 902 of support arm 900 and the rollers 914 and 904 cooperate to enable a smooth, low resistance rolling movement of the neck portion 902 relative to the support member 910.

Figure 83 illustrates an alternative preferred embodiment of the support member 910' having a plurality rollers 914' disposed within the support member
15 910'. In this embodiment no rollers 904 would need to be provided on the neck portion 902 of the support arm shown in Figure 82 to enable smooth sliding movement.

Figure 84 shows a support arm 920 in accordance with another alternative preferred embodiment of the member 910. Support member 920 includes an LCD
20 mounting member 922, such as described hereinbefore, and a neck portion 924 having a pair of longitudinally extending channels 926 facing away from each other. A support member 928 is of tubular construction and includes a pair of opposite, inwardly facing ribs 930 which ride within the channels 926 to help guide the neck portion for sliding movement. Figure 85 illustrates an embodiment 920'
25 which is identical to the embodiment shown in Figure 84 except for the use of square shaped channels 926' and square shaped ribs 930'.

Referring now to Figures 86-88, a locking system for enabling quick and easy movement of a ball joint type mount from a portrait orientation to a landscape orientation is shown. A neck 952 of a ball joint type LCD screen
30 support 950 has a keyed end 954. The end 954 resides within an opening 956 in a support arm 958. The keyed end 954 has a keyed opening 960 which is able to receive a similarly keyed member 964 of a release assembly 962.

The release assembly 962 includes a flip up handle 966 attached to a shaft 968. The shaft 968 is also attached to the keyed member 964 and moves slidably within a washer 970 separated from the handle by one or more springs 972.

5 The end 954 is captured in the opening 956 by a retainer plate 974 which is fixedly secured to the support arm 958, as also shown in Figures 87 and 88. The washer 970 is also secured to the support member 958 such that pulling on the handle 966 allows the keyed member 964 to be released from the keyed opening 960, when assembled into the arm 958, thereby permitting the keyed end 954 to be rotated while the handle 966 is pulled. In this manner the orientation
10 of the ball joint type LCD screen support 950 can be changed between two orientations. Figure 89 illustrates a partial cross section of the release assembly 962 disengaged from the keyed end portion 954.

Referring now to Figure 90, another release mechanism 980 in accordance with another alternative embodiment of the present invention is shown. This
15 embodiment is very similar to the embodiment of Figures 86-89 with the exception that automatic stops are built in to the mechanism to allow movement only between two positions 90 degrees apart from one another.

With further reference to Figure 90, two stop members 982 are fixedly disposed within a portion of a support arm 984 having a recess 985. A neck
20 portion 984 of a LCD screen mount 986 includes a pair of oppositely facing grooves formed in the neck 984 which receive the stop members 982. As can be seen in Figure 91, the grooves 988 only allow the neck 984 to rotate between two positions ninety degrees apart. The LCD screen mount 986 is also shown in Figure 92.

25 Referring further to Figure 90, an outermost end of the neck 990 includes a pair of keyed grooves 992. A key portion 994 of a release member 996 is fixedly secured to a shaft 998. A stop element 1000 is separated from a wall portion 1002 of a support arm 1004 by a pair of springs 1006. The shaft 998 extends through a hole 1008 in the wall portion 1002 and has a graspable knob
30 1110 at the end thereof. Pulling outwardly on the knob 1110 against the biasing force of the springs 1006 causes the stop element 1000 to be withdrawn from the keyed grooves 992, thus enabling the neck 984 to be turned between one of two

positions 90 degrees apart from one another while the knob 1110 is held in its pulled out position. When the knob 1110 is released, the springs 1000 bias the key portion 994 back into the grooves 992 such that the neck 984 cannot be rotated. In this regard it will be appreciated that the grooves may also form a plurality of apertures that enable the neck 984 to be rotated between two positions about 90 degrees apart.

Referring now to Figures 93-103, a display system 1120 is shown. The display system 1120 incorporates a universal ball hinge mechanism 1122 for coupling two LCD screens 1124 together and allowing rotation relative to one another about two axes extending perpendicular to each other. Release mechanisms 1126 enable the two screens to be secured in either portrait or landscape orientations. In this manner the screens can be used in a variety of orientations to fit the needs of specific applications or situations where multiple screens of information need to be displayed in certain orientations.

Referring now to Figure 104, a display system 1200 is illustrated in which a pair of LCD screens 1202 are supported on a common display arm 1204, which is in turn supported on a vertical support 1206. The vertical support 1206 is supported fixedly on a base unit 1208. With this embodiment, the LCD screens 1202 do not need to be moved closer to or farther from each other when remounted in a landscape or a portrait orientation.

In Figure 104, the dimension X_A is set equal to the dimension X_B . Thus, when the LCD screens are repositioned on the support arm 1204 in Figure 105, there is sufficient clearance to permit mounting the screens in the portrait orientation.

Referring now to Figures 106-118, a release member 1200 in accordance with an alternative preferred embodiment of the present invention is illustrated. This embodiment incorporates a shaft 1202, as illustrated in Figures 106 -108, having a plurality of teeth 1204a, 1204b and 1204c. Teeth 1204a and 1204c are each spaced 90 degrees away from the central tooth 1204b. As shown in Figure 107, each tooth 1204 preferably includes a tapered edge portion 1206.

Referring to Figures 109-116, a support member 1208 includes an opening 1210 designed to cooperate with the release member 1200 to enable the release

member to be quickly released from a locked position and moved between two positions 90 degrees apart from one another. The opening 1210 includes a stop portion 1212 having surfaces 1212a and 1212b. With brief reference to Figures 115 and 116, the opening also includes steps 1214, 1216 and 1218. The steps 1214, 1216 and 1218 are at 90 degree increments about the inner periphery of the opening 1210. Each step 1214, 1216 and 1218 is further set back from a face surface 1219, while the stop 1212 is formed so as to be flush with the surface 1219.

Referring now to Figures 109-114, the release member 1200 is illustrated being inserted into and rotated within the opening 1210. The release member 1200 fits within the opening 1210 such that steps 1204a and 1204c are positioned on opposite sides of the stop 1212. When fully inserted into a "locked" position, as shown in Figure 111, the release member 1200 cannot be turned. This is also illustrated in Figure 114. The tapered surfaces 1206 on each step 1204 also helps to wedge the steps 1204 into the opening 1210 to eliminate play when the release member 1200 is in its locked position. When the release member 1200 is partially withdrawn to the point that the arms 1204 clear the steps 1214, 1216, and 1218, as shown in Figures 112 and 113, then the entire release member 1200 can be rotated 90 degrees counterclockwise and reinserted fully into the opening 1210. The release member 1200 is shown in this orientation in Figure 114. The stop 1212 acts to prevent further rotation of the release member 1200 because of abutting contact of arm 1204c with stop 1212. If the release member 1200 is rotated from the orientation shown in Figure 114 back into the orientation shown in Figure 112, then the abutting contact between arm 1204a and stop 1212 limits the movement in this direction. Thus, the stop 1212, in connection with the arms 1204a and 1204c, limits the rotational movement of the release member 1200. The orientation of the release member 1200 relative to the opening 1210 in the two above described positions is shown in Figures 117 and 118. The steps 1214-1218 provide a means to lock the entire release member 1200 immovably in place.

Referring now to Figures 120 and 121, a lever assembly 1220 is illustrated for use with the release member 1200. The lever assembly comprises a lever

1222 which is pivotably mounted to a base element 1224. The base element 1224 is disposed within an opening 1210 in the support member 1208. In this embodiment, the opening 1210 includes a recess 1226 preferably deep enough so that the lever resides therein flush with a rear surface 1208a of the support member 1208 when the lever 1222 is in the closed position shown in Figure 119.

The lever 1222 is coupled to a locking shaft 1228 preferably by a camming mechanism which retracts the locking shaft 1228 when the lever is moved to an open position, as shown in Figure 120. The opposite end of the locking shaft 1228 is fixedly secured to the release member 1200 such as by threaded engagement with a portion of the release member 1200. The lever assembly 1220 thus forms a convenient means by which the release member 1200, and a ball joint assembly attached thereto, can be quickly and easily locked in place or unlocked. Figures 121 and 122 illustrate the lever 1222 being moved from the closed to the open position.

Referring now to Figures 123-126, another alternative embodiment of the extendable arm of Figure 82 is shown. This embodiment includes a support arm 1250 having a plurality of longitudinally extending grooves or channels 1252a-1252c (Figure 125). The channels 1252b and 1252c accept complementarily shaped shoulder portions 1254 formed in an interior surface of a support member 1256. The support member 1256 also includes a threaded opening 1258 through which a threaded portion 1260 of a locking knob 1262 is disposed. The threaded portion 1260 is fixedly secured to a knob portion 1264 and at its opposite end rotatably to a tab 1266. The tab 1266 is shaped so as to fit within the channel 1252a when the support arm 1250 is inserted into the support member 1256.

From Figures 124-126, the support arm 1250 is locked into place by simply screwing down the locking knob 1264, which clamps the arm 1250 securely within the support member 1252.

Referring now to Figure 127, the locking knob 1262 is just as easily adaptable for use with a support arm 1270 which incorporates rollers 1274. The rollers 1274 allow an even smoother rolling movement of the support arm 1270 into and out of its associated support member 1276.

Referring to Figures 128-130, a release assembly 1300 for a ball joint is

shown. The assembly 1300 includes a ball joint member 1302, a mounting block 1304, a washer assembly 1306, a retainer 1308 and an end cap 1310. Optionally, a flat washer 1312 can also be included.

5 The ball joint member 1303 includes a ball joint portion 1314 coupled via a shaft 1316 to a base member 1318. A locking shaft 1320 projects from the base member 1318. The locking shaft 1320 includes a groove 1322 formed on an end portion thereof for accepting the retainer 1308. The base member 1318 includes four registration detents 1324 spaced every 90 degrees about the periphery thereof.

10 The mounting block 1304 shown in Figures 128 and 129 includes four raised shoulder portions 1326, one at each corner thereof. The shoulder portions 1326 are further spaced so as to engage with the four registration detents 1324 when aligned with the detents 1324. A central opening 1327 provides a passage for the locking shaft 1320 to extend therethrough, and a recess 1329 in a rear surface 1331 provides room for the washer assembly 1306, the retainer 1308, the cover member 1310, and optionally the flat washer 1312, if included, to reside therein.

The assembled components are shown in Figure 130. The washer assembly 1306 preferably comprises a "wave" washer assembly which provides
20 a biasing force when compressed to maintain the ball joint member 1302 securely against the mounting block 1304. It will be appreciated that a wide variety of spring assemblies could be used to provide a suitable biasing force in lieu of the washer assembly 1306. When assembled, the shoulder portions 1326 are held securely within the registration detents 1324 when aligned therewith, thus
25 preventing rotation of the ball joint member 1302.

When it is desired to reposition the ball joint member 1302, a pulling force is exerted on the member 1302 to momentarily urge it away from the mounting block 1304. While in this position, the ball joint member 1302 is rotated either clockwise or counterclockwise. As the ball joint member 1302 is rotated, the
30 shoulders 1326 will automatically "snap" into the registration detents 1324 after 90 degrees of rotation. The ball joint member 1302 can thus be positioned and held within any of four positions, wherein each position is 90 degrees from its next

adjacent position. Advantageously, no tools or partial disassembly of the system 1300 is required to rotate the ball joint member 1302.

Referring now to Figures 131-133, an arrangement is illustrated for attaching two LCD screens 1352 and 1354 of a dual screen LCD display system 1350 in such a manner that the screens can be supported by a pair of ball joint type supports on a common support arm 1356, and centered along a horizontal midpoint of each, or aligned such that the lower or upper edges of each LCD screen are aligned with each other.

In Figure 133, the distance X_a is set equal to X_b , when the two LCD screens 1352 and 1354 are to be aligned along their upper horizontal edges. This produces hypotenuse X_c . Distance Y_1 represents the desired clearance between the two LCD screens 1352, 1354. Distance F represents the difference in distance by which LCD screen 1354 exceeds LCD screen 1352. Distance X_b is $1/2$ the total distance G of LCD screen 1352. When LCD screen 1352 is positioned in the landscape orientation, its top edge is aligned with the top edge of LCD screen 1354. When it is removed from its ball joint support, the ball joint support rotated 90 degrees clockwise, and the screen 1352 is rotated 90 degrees clockwise and reattached in the portrait mode, edge 1352a will be aligned with edge 1354a of screen 1354. Conversely, LCD screen 1354 could be removed, its ball joint support rotated 90 degrees clockwise, the screen 1354 rotated likewise, and resecured to its ball joint such that edge 1352a of screen 1352 and edge 1354a of screen 1354 are both aligned parallel to each other, which will place edges 1352a' and 1354a' in horizontal alignment with each other.

Referring to Figure 131, the LCD screens 1352 and 1354 can be aligned along edges 1352c and 1354c if the mounting point of screen 1352 is moved a distance d in the X direction and a distance c in the Y direction, and where distance c equals d , and c plus d is further equal to G . The effect of this is that the pivot point of LCD screen 1352 moves along the hypotenuse X_c a small distance, thereby allowing a shorter support arm 1356 to be used. Note H is also $1/2$ the distance of the LCD screen 1352 total height. Distance H is also $1/2$ the total width of LCD screen 1354. If the LCD screen 1352 is removed, rotated 90 degrees clockwise and reattached to the support arm 1356, then the edges 1352d

and 1354d will be horizontally aligned. It will be appreciated that an arm 1356 having the same length as the arm shown in Figure 133 could be used, but that such a longer arm would require that the ball joint supports which support the LCD screens 1352 and 1354 on the arm 1356 be mounted on the arm for sliding movement so they can be positioned closer to one another than the spacing shown in Figure 133. In this manner the ball joints could be readjusted closer to each other when the screens 1352 and 1354 are to be aligned as shown in Figure 131.

Referring to Figure 132, the LCD screen 1352 can be positioned perfectly centered along the vertical side of LCD screen 1354, if the pivot point is located offset from a horizontal midpoint of screen 1352 by a distance b in the X direction and a distance a in the Y direction, and if b is equal to a , and the sum of b and a equals $B2$. Since the LCD screen 1352 is centered along the vertical edge of screen 1354, $B2$ is equal to $B1$. In this instance, $B1$ and $B2$ will each be $1/2$ of distance F designated in Figure 133. The LCD screen 1352 can also be removed, its ball joint support rotated 90 degrees clockwise, and the screen 1352 reattached to the support arm 1356, which will put edge 1352d thereof in horizontal alignment with edge 1354d of screen 1354.

It will also be noted that the support arm 1356 shown in Figure 132 also is shorter than the support arm 1356 shown in Figure 133. By therefore using the above-described guidelines, the ball joint supports of each of the LCD screens 1352 and 1354 can be mounted at specific points on the rear surface of each LCD screen 1352 and 1354, and spaced apart on the support arm 1356, such that the two screens can be aligned together in various orientations when one is in the portrait orientation and the other is in a landscape orientation. It will also be appreciated that while the above-described dimensions have been discussed only with regard to LCD screen 1352, that screen 1354 will need to be supported, in each of Figures 131-133, with the same dimensional requirements as its accompanying screen 1352 in each figure. Also, the distances $Y1$, $Y2$ and $Y3$ shown in Figures 133, 132 and 131, respectively, need to be taken into account in each instance when determining the needed spacing between the two pivot points on the support arm 1356.

Referring now to Figures 134-139, a ball joint assembly 1400 is illustrated which enables rotation of a neck portion 1402 relative to a base portion 1404 when the neck portion is urged into the position shown in Figures 136 and 137. This feature is useful for enabling an LCD screen to be moved from a portrait orientation into a landscape orientation, or vice versa, without the need to first physically detach the LCD screen from its ball joint support assembly, while still permitting booking of the two screens relative to each other. It will be appreciated that with the ball joint support assemblies described previously herein, rotation of one of two closely positioned LCD screens first requires removal of the screen before it can be rotated. After being rotated into the desired orientation, the LCD screen would be reattached. The problem of sufficient clearance between the two LCD screens, and the limitations on the construction of the ball joint assembly itself, did not permit one of the LCD screens to simply be rotated into another orientation.

Referring further to Figures 134 and 135, the ball joint assembly 1400 overcomes this shortcoming by providing a groove formed in the base member of the assembly 1400 which enables the neck portion 1402 to be rotated once the neck is moved into a booked position. To accomplish this, the neck portion 1402 includes a pin 1406 fitted in the ball member 1408 thereof. The pin 1406 is restrained for movement within a channel 1410. The channel enables precise booking movement of the LCD screen (not shown) attached to a keyed end portion 1412 of the neck portion 1402.

Formed within the base portion perpendicularly to channel 1410 is a groove 1414. Groove 1414 is sized to accept the pin 1406 once the pin is moved into alignment with the groove 1414. This alignment is shown in Figures 136 and 137. When the pin 1406 is aligned as shown in Figures 136 and 137, the LCD screen will be booked outwardly such as shown in Figure 141 by screen 1416. Once booked into this orientation, LCD screen 1418 will not interfere with subsequent rotation of screen 1416.

Referring to Figures 138-139 and 140-143, LCD screen 1416 can then be rotated counterclockwise into the portrait orientation without interference from screen 1418. The groove 1414 thus enables rotation of the ball member 1408 but

only once the screen 1416 has been booked outwardly a sufficient degree to place the pin 1406 in alignment with the groove 1406. This provides the advantage of preventing accidental rotation of the LCD screen 1416, since the user is required to move the screen 1416 to an outwardly booked position (Figure 5 141) before any rotation can be effected. The fully rotated screen 1416 is illustrated in Figures 142 and 143.

If the ball joint assembly is orientated on its support arm 1420 in Figures 144-147 such that the groove 1406 is 180 degrees displaced from the orientation in Figures 136 and 137, then screen 1418 in Figures 144-147 can be similarly 10 rotated once it is booked outwardly as shown in Figure 145. Accordingly, the ball joint assembly 1400 enables each of the screens 1416 and 1418 to be rotated between the portrait and landscape orientations once they are booked outwardly a sufficient degree. As such, there is no need to first remove either screen if it needs to be repositioned.

15 Referring now to Figures 148 and 149, a portion of a base assembly 1500 for an LCD screen is illustrated. The base assembly 1500 incorporates a built in control panel, which is shown in enlarged fashion in Figure 1502. The control panel incorporates an ON/OFF switch 1504, a built in speaker 1506, a volume "UP" button 1508 and a volume "DOWN" volume button 1510 for enabling easy 20 adjustment of the volume of the speaker 1506. A "SELECT" button 1512 enables the user to select which one of several LCD screens being supported can be adjusted for picture brightness, centering, etc. A "RESET" button 1514 enables the user to reset the various visual adjustments (i.e., contrast, brightness, etc.) to default settings. A dial 1516 enables the user to scroll through various choices 25 provided on the selected screen in menu format. Standby LED 1518 provides an provide an indication that one or more of the screens are powered on. An infrared sensor 1520 enables use of the display system with a wireless keyboard. It will be appreciated that not all of the features of the control panel 1502 need to be included and, alternatively, that other switches or components could just as easily 30 be incorporated if needed.

Referring now to Figure 152, a display system 1550 is shown which is substantially similar to the display system 400 of Figure 65 with the exception of

a camera 1552 mounted in a support arm 1554 thereof. The camera enables convenient video conferencing to be accomplished from the display system 1550.

5 The camera 1552 includes a flexible tubular sheath 1556 which holds the orientation it is placed in. At one outermost end of the sheath 1556 is mounted an optical camera 1558. The flexibility of the sheath 1556 enables the camera 1552 to be adjusted to precisely the desired height to suit the user seated in front of the display system 1550.

10 Referring to Figure 153, an alternative preferred embodiment of the camera 1552' is shown in which a microphone 1560 is attached to the optical camera 1558'.

Figure 154 illustrates the camera 1552 disposed between a pair of LCD screens 1562. Figure 155 even better illustrates the flexibility of the camera 1552. The flexibility of the sheath 1556 enables the optical camera 1558 to be pointed at a desired angle, whether at the user or down on a document placed on a table supporting the display system 1550. Figure 156 illustrates in enlarged fashion the sheath 1556 of the camera 1552 exiting through an opening 1564 in the arm 1554.

20 Referring now to Figure 157, a display system 1600 in accordance with another alternative preferred embodiment is shown. The system 1600 includes a pair of LCD screens 1602, with one of the screens including a built-in camera 1604 placed within the interior area of the bezel 1606 of the LCD screen.

25 Figure 158 shows a clip 1608 having a built-in camera head 1610 suitable for coupling to the bezel of one of the LCD screens 1602. The clip 1608 is shown in Figure 159 secured to a bezel 1612 of the LCD screen 1602. Advantageously, the clip 1608 can be moved around the bezel 1612 and secured at different positions on the bezel 1612 to best suit the position of the LCD screen 1602 relative to the user.

CLAIMS

I claim:

1. A display system comprising:
5 a first liquid crystal display (LCD) screen;
a second liquid crystal display (LCD) screen;
a support arm for supporting the first and second LCD screens; and
a first quick release assembly adapted to releasably secure one of said first
and second LCD screens to said support arm such that said one LCD screen can
10 be quickly uncoupled from said support arm, wherein mechanical and electrical
connections to said one LCD screen are simultaneously disconnected.
2. The display system of claim 1, wherein said quick release assembly
comprises a first docking member secured to said support arm;
a second docking member secured to the one LCD screen; and
15 wherein the second docking member is adapted to slidably engage the first
docking member to mechanically and electrically couple the one LCD screen to
the support arm.
3. A laptop computer comprising
a housing;
20 a keyboard/processor housed by said housing;
a first liquid crystal display (LCD) screen;
a second liquid crystal display (LCD) screen pivotably secured to the first
LCD screen and adapted to be folded at least partially over the first LCD screen
when said laptop computer is not being used.
- 25 4. A display system for a computer comprising:
a first liquid crystal display (LCD) screen;
a second liquid crystal display (LCD) screen;
a support arm for supporting said first and second LCD screens in a side-

by-side arrangement;

a first member for pivotably supporting said first LCD screen on said support arm;

5 a second member for pivotably supporting said second LCD screen on said support arm;

and wherein said first LCD screen is further pivotably supported at a point on a housing thereof enabling said first LCD screen to pivot from a landscape mode to a portrait mode without interference from said second LCD screen.

10 5. A display system for a computer system, the display system comprising:
a first liquid crystal display (LCD) screen;
a second liquid crystal display (LCD) screen;
a support arm for supporting both of said LCD screens thereon;
pivoting mechanisms for enabling each of said LCD screens to be pivoted thereon between portrait and landscape orientations; and
15 said support arm having a first component and a second component, wherein said first component is moveable relative to said second component to extend the effective overall length of said support arm to enable one of the LCD screens to be pivoted without physical interference from the other one of the LCD screens.

20 6. A display system for a computer system, said display system comprising:
a base portion;
a vertical support column extending from said base system;
and said base portion including at least one audio speaker and a plurality
25 of controls for controlling operation of the display system.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 6




FIG. 5




FIG. 7




FIG. 8







FIG. 9








FIG. 15




FIG 16




FIG. 17










FIG. 18

9/55





10/55





12/55



13/55




FIG. 26




FIG. 27

14/55




FIG. 29




FIG. 28

15/55




FIG. 30




FIG. 31




FIG. 32

16/55

FIG 33




FIG 34





FIG 35

FIG 36






FIG 38




FIG 39

18/55

FIG 40




FIG 41





FIG 42



19/55

FIG 43





FIG 43A







FIG 46

FIG 47

21/55

FIG 48





FIG 49

22/55

FIG 50





FIG 51









FIG 52



24/55



25/55

FIG 58










FIG 59

26/55

FIG 60



27/55
















FIG 68






30/55












FIG 89





FIG 90

35/55

FIG 91















FIG 92



37/55





39/55

FIG 106





FIG 107








FIG 108

40/55











FIG 119







FIG 120

FIG 121






FIG 126





FIG 127




FIG 131





FIG 132







FIG 133



50/55









FIG 144

FIG 146




FIG 145




FIG 147

51/55

FIG 148











FIG 149





53, 55



54/55





INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/30733

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : F16L 3/00

US CL : 248/122.1; 345/173

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 248/122.1; 345/173, 103, 200, 156, 168, 169, 179, 211, 350, 901, 905; 361/681

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
EAST, WEST

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X --- Y	US 5,687,939 A (MOSCOVITCH) 18 NOVEMBER 1997, COL.3, LINES 13-21, FIGURES 1-6 at 10, 12, 14, 16, 18, 20, 22, COL.3, LINES 37-54, FIGURES 8-11 at 14, 16, 18, 50, 52, COL.4, LINES 61 THROUGH COL.5, LINES 1-15, FIGURES 3-6.	1, 2, 4, 5, ----- 6
X ---- Y	US 5,847,698 A (REAVEY et al) 08 DECEMBER 1998, COL.4, LINES 48-55, FIGURE 1 at 15, 16, COL.5, LINES 13-20, COL.5, LINES 33-46, COL.2, LINES 4-11.	3 ---- 6

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* "A"	Special categories of cited documents: document defining the general state of the art which is not considered to be of particular relevance	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E"	earlier document published on or after the international filing date	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means	"A"	document member of the same patent family
"P"	document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

01 MAY 2000

Date of mailing of the international search report

25 MAY 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

UCHENDU O. ANYASO

Telephone No. (703) 306-5934